

Portaflow SE Portable Transit Time Flow Meter

Approximate shipping weight: 18 lbs / 8 kg

STANDARD FEATURES:

- PTSE1 sensor set for pipe diameter 2-40" ID (50-1000 mm)
- Sensor cable - 6 ft (2 m) coaxial pair with connectors
- Sensor mounting kit with guide rail, hardware and ultrasonic couplant
- enclosure - NEMA4X (IP66), ABS
- carrying case - padded aluminum
- display - backlit LCD with graphics capability, volumetric flow, velocity, total, operating menu, battery and signal level
- calibration - built-in 16-key menu system
- outputs - 0/4-20mA (750 ohms)
- RS232-C serial
- data logger - 50,000 data point capacity
- power input - built-in NMH battery rated for up to 8 hrs operation
- external charger 100-240VAC 50/60Hz
- 1 Manual - Installation and Operation

OPTIONS AND ACCESSORIES

QTY	CODE	DESCRIPTION	
	PTSE1	Replacement Sensor set	
	PTSC1	Replacement sensor Cables pair, 6 ft. (3 m) with locking connectors	
	PTG1	Replacement stainless steel Guiderail with chains	
	PTDC1	Replacement stainless steel diagonal mounting Clips with chains (for large pipes)	
	CC	Coupling Compound - Dow Corning Silicone Compound 150 g. (5.3 oz) tube	
	MNL	Additional Manuals (One supplied with each unit)	

Standardowa dostawa : 3-4 tygodnie (+ 10% dla RUSH - przyspieszona dostawa 2-3 tygodnie)

PRODUCENT **Greyline Instruments Inc**

DYSTRYBUCJA w Polsce

Elektro-Trading Sp. z o.o.

44-109 Gliwice , ul. Mechaników 9

Tel: 032 734-55-72

www.elektro-trading.com.pl

Tel/Fax : 032 734-55-70

et@elektro-trading.com.pl